

IN THE CLAIMS:

Cancel Claims 1-5 without prejudice.

- Sub 17
1. (Cancelled)
 2. (Cancelled)
 3. (Cancelled)
 4. (Cancelled)
 5. (Cancelled)

6. (Currently Amended) A cross-correlated signal processor comprising:

B1
cont

(a) means for cross-correlating a first input signal with a second input signal to generate cross-correlated a fraction, or one or more than one symbol synchronous and/or asynchronous time constrained signal (TCS) response and cascaded long response (LR) filtered signal symbols of one or more input signals with signal symbols of a quadrature-phase shifted signal of the in-phase signal, and providing in-phase (I) and quadrature-phase (Q) shifted output signals adapted for Bit Rate Agile (BRA), cascaded mis-matched (ACM) Modulation-Demodulation (Modem) Format Selectable (MFS) and Code Selectable (CS) processing, the first input signal comprising a fraction or one or more than one symbol synchronous and/or asynchronous time constrained signal (TCS) response and cascaded long response (LR) filtered signal symbols of one or more input signals, and the second input signal comprising signal symbols of a quadrature-phase signal, the cross-correlated in-phase (I) and quadrature-phase (Q) output signals generated according to the following schedule:

- cross-correlated
- (i) when the in-phase channel signal is zero, the quadrature-phase shifted signal is close to the maximum amplitude normalized to one (1);
 - (ii) when the in-phase channel signal is non-zero, the maximum magnitude of the quadrature-phase shifted signal is reduced from 1 (normalized) to A, where $0 \leq A \leq 1$;
 - (iii) when the quadrature-phase channel signal is zero, magnitude of the in-phase signal is close to the maximum amplitude; and
 - (iv) when the quadrature-phase channel signal is non-zero, the in-phase signal is reduced from 1 (normalized) to A, where $0 \leq A \leq 1$;

(b) means for quadrature modulating the cross-correlated in-phase and quadrature-phase output signals to provide a cross-correlated quadrature modulated output signal, the means for quadrature modulating including a BRA, MFS and BRA filter set;

(c) controller and selector controlling means and signal selection means for BRA rate, MFS and CS processor selection and processor selection and means for selection for Linear and/or Non-Linearly Amplified (NLA) baseband and/or of Quadrature modulated signals selection;

(d) coupling port means for coupling the cross-correlated quadrature modulated output signal to the a transmission medium;

(e) a BRA, MFS and CS quadrature demodulator;

(ef) a receiver port for connection of the received cross-correlated signal to the BRA, MFS and CS demodulator; and

(f) a BRA, MFS and CS quadrature demodulator; and

(g) a Mis-Matched (MM) demodulator filter set for BRA, MFS and CS in which the said a filter set of the quadrature demodulator filter set is MM mis-matched to the that of the BRA, MFS and BRA filter set of the means for quadrature modulating modulator.

Cancel claim 7 and Claims 10-42 without prejudice or disclaimer, claims 8-9 were previously cancelled.

- 7. (Cancelled)
- 8. (Cancelled)
- 9. (Cancelled)
- 10. (Cancelled)
- 11. (Cancelled)
- 12. (Cancelled)
- 13. (Cancelled)
- 14. (Cancelled)
- 15. (Cancelled)
- 16. (Cancelled)

B

A-66732-3/RMA

17. (Cancelled)
18. (Cancelled)
19. (Cancelled)
20. (Cancelled)
21. (Cancelled)
22. (Cancelled)
23. (Cancelled)
24. (Cancelled)
25. (Cancelled)
26. (Cancelled)
27. (Cancelled)
28. (Cancelled)
29. (Cancelled)
30. (Cancelled)
31. (Cancelled)
32. (Cancelled)
33. (Cancelled)
34. (Cancelled)
35. (Cancelled)
36. (Cancelled)
37. (Cancelled)
38. (Cancelled)
39. (Cancelled)
40. (Cancelled)
41. (Cancelled)
42. (Cancelled)

B1
Cont

6

43. (Currently Amended) A cross-correlated signal processor comprising:

(a) a cross-correlator for cross-correlating a first input signal with a second input signal to generate cross-correlated a fraction, or one or more than one symbol synchronous and/or asynchronous time constrained signal (TCS) response and cascaded long response (LR) filtered signal symbols of one or more input signals with signal symbols of a quadrature phase shifted signal of the in-phase signal, and providing in-phase (I) and quadrature-phase (Q) shifted output signals adapted for Bit Rate Agile (BRA), cascaded mis-matched (ACM) Modulation-Demodulation (Modem) Format Selectable (MFS) and Code Selectable (CS) processing, the first input signal comprising a fraction or one or more than one symbol synchronous and/or asynchronous time constrained signal (TCS) response and cascaded long response (LR) filtered signal symbols of one or more input signals, and the second input signal comprising signal symbols of a quadrature-phase signal, the cross-correlated in-phase (I) and quadrature-phase (Q) output signals generated according to the following schedule:

(i) when the in-phase channel signal is zero, the quadrature-phase shifted signal is close to the maximum amplitude normalized to one (1);

(ii) when the in-phase channel signal is non-zero, the maximum magnitude of the quadrature-phase shifted signal is reduced from 1 (normalized) to A, where $0 \leq A \leq 1$;

(iii) when the quadrature-phase channel signal is zero, the in-phase signal is close to the maximum amplitude; and

(iv) when the quadrature-phase channel signal is non-zero, the in-phase signal is reduced from 1 (normalized) to A, where $0 \leq A \leq 1$;

(b) a signal modulator for quadrature modulating the cross-correlated in-phase (I) and quadrature-phase (Q) output signals to provide a cross-correlated quadrature modulated output signal, the signal modulator including a BRA, MFS and BRA filter set;

(c) a controller and selector for selecting at least one of: (1) at least one of or any combination of: BRA rate, MFS, and CS processors; selection, and selection for (2) at least one of Linearly and/or Non-Linearly Amplified (NLA) baseband signals, and/or of (3) at least one of

linearly, non-linearly, or partially linearly and partially non-linearly amplified quadrature modulated signals;

(d) a first ~~signal-coupling~~ for coupling a the cross-correlated quadrature modulated output signal to a transmission medium;

(e) a second ~~signal-coupling~~ for coupling a received cross-correlated quadrature modulated signal from the transmission medium to a receiver having a receiver port;

~~(f) a BRA, MFS, and CS quadrature demodulator;~~

(fg) a the receiver port for connection of the received cross-correlated quadrature modulated signal to the BRA, MFS, and CS demodulator; and

~~(g) a BRA, MFS and CS quadrature demodulator; and~~

(h) a Mis-Matched (MM) demodulator filter set for BRA, MFS and CS in which the said demodulator filter set is MM mis-matched to that of the BRA, MFS and BRA filter set of the signal modulator.

Cancel Claims 44-56 without prejudice or disclaimer.

- 44. (Cancelled)
- 45. (Cancelled)
- 46. (Cancelled)
- 47. (Cancelled)
- 48. (Cancelled)
- 49. (Cancelled)
- 50. (Cancelled)
- 51. (Cancelled)
- 52. (Cancelled)
- 53. (Cancelled)
- 54. (Cancelled)
- 55. (Cancelled)
- 56. (Cancelled)

b

57. (Currently Amended) The cross-correlated signal processor of Claim 43, wherein the cross-correlated signal processor is adapted to process (i) an first-in-phase channel-signal set component; and (ii) a second-quadrature-phase channel-signal set-component that is generated as a phase-shifted version of the first in-phase channel-signal; and

the in-phase and quadrature-phase channel-signals components characterized in that: (i) when the in-phase channel-signal is zero, the quadrature-phase shifted-signal is close to the maximum amplitude normalized to one (1); (ii) when the in-phase channel-signal is non-zero, the maximum magnitude of the quadrature-phase shifted-signal is reduced from 1 (normalized) to A, where $0 \leq A \leq 1$; (iii) when the quadrature-phase channel-signal is zero, the in-phase signal is close to the maximum amplitude; and (iv) when the quadrature-phase channel-signal is non-zero, the in-phase signal is reduced from 1 (normalized) to A, where $0 \leq A \leq 1$; and

B1 Cont
~~the first in-phase and second quadrature-phase signal set components derived from at least one signal stream as a fraction a symbol or from one or more than one symbol as a time constrained signal (TCS) response and cascaded long response (LR) filtered signal symbols of one or more input signals with signal symbols of a quadrature-phase shifted signal of the in-phase signal.~~

58. (Currently Amended) A bit-rate agile (BRA) and modem format and code selectable (MFS and CS) signal pair comprising:

an first-in-phase channel signal set component; and
a second-quadrature-phase channel signal set-component that is generated as a phase-shifted version of the first in-phase channel-signal;

the in-phase and quadrature-phase channel signals characterized in that: (i) when the in-phase channel signal is zero, the quadrature-phase shifted-channel signal is close to the maximum amplitude normalized to one (1); (ii) when the in-phase channel signal is non-zero, the maximum magnitude of the quadrature-phase shifted-channel signal is reduced from 1 (normalized) to A, where $0 \leq A \leq 1$; (iii) when the quadrature-phase channel signal is zero, the in-phase channel signal is close to

A-66732-3/RMA

the maximum amplitude; and (iv) when the quadrature-phase channel signal is non-zero, the in-phase signal is reduced from 1 (normalized) to A, where $0 \leq A \leq 1$; and

BI
cancel

the first-in-phase and second-quadrature-phase channel signal set components are derived from at least one input signal stream as a fraction of a symbol or from one or more than one symbol as a time constrained signal (TCS) response and cascaded long response (LR) filtered signal symbols, ~~of one or more input signals with signal symbols of a quadrature-phase shifted signal of the in-phase signal.~~
